

# Q-Wash™ 560Z-LED



Q-Wash™ 560Z-LED is a best-in-class moving yoke wash with a wide zoom range and a variable beam angle. It powers out an impressive 13,100 lux at 5 meters. The incorporation of 91 high intensity and calibrated RGBWA Cree LEDs ensures a uniform wash, excellent color rendering and a vast color palette of soft pastels and vivid hues.

## FEATURES

- 12, 14 or 15 DMX channels
- 9° to 37° zoom
- RGBWA LEDs
- RGBWA color mixing
- Electronic shutter
- Electronic dimmer
- All functions reset over DMX
- Move-in-black over DMX or on display
- Color macros with speed adjustment
- IP rating: IP20
- Lightweight and easy to install
- 3- and 5-pin XLR DMX connections
- User-selectable pan/tilt ranges
- Automatic pan/tilt correction

## SPECIFICATIONS

- DMX Channels: 12, 14 or 15
- Data Connectors: 3- and 5-pin XLR
- Light Source: 91 LEDs (22 red, 23 green, 22 blue, 12 white, 12 amber) 273 W, (800 mA), 50,000 hours life expectancy
- Pan and Tilt: 540°/270°
- Automatic Pan/Tilt Correction: Yes
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 6° to 32°
- Field Angle: 9° to 37°
- Zoom Angle: 9° to 37°
- Dimming Modes: 5
- Illuminance (9°): 13,100 lux @ 5 m
- Illuminance (37°): 917 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to IEC
- Power Input: IEC
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 309 W, 2.7 A @ 120 V, 60 Hz
- Power and Current: 304 W, 2.6 A @ 208 V, 60 Hz
- Power and Current: 289 W, 1.4 A @ 230 V, 50 Hz
- Weight: 21.2 lb (9.62 kg)
- Dimensions: 13.3 x 9.1 x 14.2 in (339 x 232 x 361 mm)
- Approvals: CE, ETLC