

Amhaze Whisper



SPECIFICATIONS

Dynamic Effects

- Fan Speed: 77 cfm
- Low Fluid Shutdown: Yes

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- CTC-50SC
- Neutrik etherCON cables
- 3- and 5-pin XLR DMX cables

FEATURES

- Professional water-based haze machine
- Quiet operation for theatrical and studio usage
- Removable vent louver for directional haze flow
- Tour-ready with a rugged road case and M12 threaded rigging insert
- Efficient fluid consumption lasts up to 11.5 hours on a single fluid container
- Achieve continuous variable haze output and blower speed, adjusted via DMX or the manual knobs

Construction / Physical

- Dimensions: 19.29 x 14.96 x 10.62 in (490 x 380 x 270 mm)
- Weight: 34.1 lb (15.5 kg)
- Exterior Color: Black
- Tank Capacity: 0.92 gal (3.5 l)
- Fluid Consumption: 5.06 ml/min (0.08 gallons/hour)
- Maximum Run time: 11.5 hours @ full volume

Connections

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX
- DMX Channels: 2
- Modes/Personalities: 1 personality
- On-Board Control: Yes

Electrical

- Input Voltage: 120 VAC, 50/60 Hz or 230 VAC, 50 Hz
- Power and Current: 1070 W, 8.5 A @ 120 V, 50/60 Hz
- Power and Current: 1285 W, 8.5 A @ 230 V, 50 Hz
- Heat-up Time: 30 sec

Certifications / Qualifications

- CE
- IP Rating: IP20, dry location
- Thermal Dissipation @ 120V: 3,650 BTU per hour (max)
- Thermal Dissipation @ 230V: 4,385 BTU per hour (max)

What's Included

- Amhaze Whisper
- Seetronic Powerkon IP65 power cord