



Ovation F-265WW

Ovation F-265WW is a high-power Fresnel-style fixture utilizing our efficient warm white LED system to project a bright, beautifully soft, high CRI (95+) field of light ideal for theatres and television studios. A motorized zoom with a 27°-68° field angle and the light output can be controlled via DMX, onboard dials, RDM, adjustable PWM and an easy to navigate OLED full text display.



At a Glance

- Warm white fresnel with output comparable to an 8", 2,000 W Fresnel
- Soft and even field of light
- 16-bit dimming resolution for smooth fades
- Virtually silent operation for use in any situation
- Motorized zoom angle between 27° to 68°, manually or via DMX

Specifications

Optical

- Light Source: 1 LED (WW) 230 W, (3.6 A), 50,000 hours life expectancy
- Color Temperature (at full): 3142 K
- CRI: 96
- Beam Angle: 16° to 46°
- Field Angle: 27° to 68°
- Zoom Angle: 27° to 68°
- Lumens (27°): 9,283
- Lumens (68°): 12,802
- Illuminance (27°): 4,010 lux @ 5 m
- Illuminance (68°): 1,162 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 30 Hz
- Dim Modes: 4

Construction / Physical

- Dimensions: 15.11 x 12.59 x 17.71 in (384 x 320 x 450 mm)
- Weight: 17.2 lb (7.9 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, Aluminum die-cast
- Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Protocol(s): DMX, RDM
- DMX Channels: 1, 2, 2 or 5
- Modes/Personalities: 4 personalities (1, 2, 2, 5)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 7 units @ 120 V; 12 units @ 208 V; 13 units @ 230 V
- Power and Current: 227 W, 1.88 A @ 120 V, 60 Hz
- Power and Current: 234 W, 1.11 A @ 208 V, 60 Hz
- Power and Current: 235 W, 1.01 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET, FCC
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- Ovation F-265WW

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN

- Neutrik powerCON power cord
- Gel Frame

- Neutrik® powerCON® cables
- 3-pin or 5-pin DMX Cables
- Color Blending Filters: DF60X1D, DF20D
- Ovation F7.5" Barndoor

Ordering Info

- Item Code: (120 V): 03031438 ; (230 V): 03031439