



Ovation F-95WW

Ovation F-95WW delivers a beautiful soft flat field with high-quality glass optics. Ovation F-95WW is built to work on its own and jointly with the larger Ovation F-165WW. A massive zoom range of 21° to 83° and a beautifully soft, warm white wash with high CRI make it a versatile replacement for aging six-inch Fresnels. A virtually quiet operation and smooth 16-bit dimming control make it a perfect choice for theatrical and/or studio applications. Manual override for dimming and a manually adjustable zoom allow you to add a beautifully soft light where needed.



At a Glance

- 16-bit dimming resolution for smooth fades
- Flat, even field of light
- Virtually silent operation for use in any situation
- Simple and complex DMX channel profiles for programming versatility
- Manually controlled variable zoom angle between 21° to 83°

Specifications

Optical

- Light Source: 9 LEDs (WW) 10 W, (2.8 A), 100,000 hours life expectancy
- Color Temperature (at full): 3199 K
- CRI: 91
- Beam Angle: 11° to 60°
- Field Angle: 21° to 83°
- Zoom Angle: 21° to 83°
- Lumens (21°): 1,681
- Lumens (83°): 3,741
- Illuminance (21°): 1,430 lux @ 5 m
- Illuminance (83°): 133 lux @ 5 m
- PWM Frequency: 600 Hz

Construction / Physical

- Dimensions: 12.8 x 11 x 16.5 in (325 x 279 x 420 mm)
- Weight: 13.4 lb (6.1 kg)
- Exterior Color: Black
- Gel Frame Size: 6.25 in/159 mm

Control

- Control Protocol: DMX
- DMX Channels: 1, 2 or 3
- Modes/Personalities: 3 personalities (UNO, DOS, STD.P)

Certifications / Qualifications

- CE, MET
- IP Rating: IP20, dry location

What's Included

- Ovation F-95WW
- Neutrik powerCON power cord
- Gel frame (6.25 in/159 mm accessories)

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Manual
- Focus: Manual
- Strobe Rate: 0 to 20 Hz
- Dim Modes: 5
- Dim Curves: 4

Connections

- Power Connection: Edison plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 15 units @ 120 V; 25 units @ 208 V; 28 units @ 230 V
- Power and Current: 108 W, 0.89 A @ 120 V, 60 Hz
- Power and Current: 110 W, 0.53 A @ 208 V, 60 Hz
- Power and Current: 110 W, 0.48 A @ 230 V, 50 Hz

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Neutrik powerCON cables
- 3-pin or 5-pin DMX Cables
- Color Blending Filters: DF60X1D, DF20D

- Ovation F6.25" Barndoor