

# Ovation SP-300CW



## SPECIFICATIONS

### Optical

- Light Source: 1 LEDs (CW) 260 W, (3.6 A), 5,640 K, 50,000 hours life expectancy
- Color Temperature (at full): 5640 K
- CRI: 88
- Beam Angle: 9° to 13°
- Field Angle: 9° to 17°
- Zoom Range: 9° to 17°
- Illuminance (Narrow): 15,400 lux @ 5 m
- Illuminance (Wide): 7,070 lux @ 5 m
- PWM Frequency: 2300 Hz

### Dynamic Effects

- Colors: 6 + white
- Dimmer: Manual, Linear
- Zoom: Manual
- Focus: Manual
- Iris: 24-leaf, full blackout

## FEATURES

- High power LED followspot with stand for mid-sized venues
- 5,500 K cool white spot with 9° to 17° zoom
- Full blackout, 24-leaf iris
- Manual linear dimmer
- 6-position, removable color changer
- Virtually silent operation for use in studio and theatre applications
- Easy access hatch for cleaning optics

## Construction / Physical

- Dimensions: 44.7 x 13.9 x 15.8 in (1,137 x 354 x 403 mm)
- Dimensions (Stand with fixture, optimal open): 46.8 x 13.98 x 62.4 in (1,189 x 355 x 1,585 mm)
- Diameter (Stand with fixture, optimal open): 33.8 in (stand) 52.8 in (fixture)
- Dimensions (Stand with fixture, max open): 46.8 x 13.98 x 81.6 in (1,189 x 355 x 2,073 mm)
- Diameter (Stand with fixture, max open): 39.6 in (stand) 52.8 in (fixture)
- Weight: 52.8 lb (24 kg)
- Exterior Color: Black
- Housing Material: Steel

## Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon (powerCON Compatible)
- Power Input: Seetronic Powerkon (powerCON Compatible)
- Cable Length (power): 5 ft (1.5 m)

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 223 W, 2.22 A @ 100 V, 60 Hz
- Power and Current: 207 W, 1.73 A @ 120 V, 60 Hz

- Power and Current: 197 W, 1.03 A @ 208 V, 60 Hz
- Power and Current: 197 W, 0.94 A @ 230 V, 50 Hz
- Power and Current: 194 W, 0.90 A @ 240 V, 50 Hz

## Certifications / Qualifications

- CE, MET, FCC
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## What's Included

- Ovation SP-300CW
- Seetronic Powerkon IP65 power cord
- Tripod stand
- Starter pack of gels