



# STRIKE 1

Strike 1 is a big, bold, outdoor-ready blinder powered by an intense 230 W warm white LED source. It is also an awesome strobe and a wide area floodlight. Its IP rated fan keeps it cool enough for use as a wash while IP rated direct power and DMX connections eliminate undesirable whips. An emulated “amber shift” warms the color temperature of the light as it dims to mimic incandescent lights perfectly.



## At a Glance

- Intense single pod blinder/strobe rated IP65 for all-weather use
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on-the-fly
- Beautiful warm glow made possible with emulated “red shift” to mimic incandescent fixtures
- Multi-bracket allows you to create multi-fixture banks with ease
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM) control to eliminate flicker on camera
- RDM (Remote Device Management) for added flexibility

# Specifications

## Optical

- Light Source: 1 LED (WW) 230 W, (4.1 A), 2688 K, 50,000 hours life expectancy
- Light Source: 8 LEDs (Amber) 2 W, (0.7 A), 50,000 hours life expectancy
- Color Temperature (at full): 2688 K
- Color Temperature (at 10%): 1941 K
- CRI: 93
- Beam Angle: 30°
- Field Angle: 51°
- Illuminance: 1,119 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 25,000 Hz

## Dynamic Effects

- Dimmer: Electronic
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

## Construction / Physical

- Dimensions: 14.96 x 7.40 x 14.61 in (380 x 188 x 371 mm)
- Weight: 18.8 lb (8.6 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 8.87 in (225 mm)

## Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

## Control

- Protocol(s): DMX, RDM
- DMX Channels: 3, 4, 5 or 6
- Modes/Personalities: 4 personalities (3ch, 4ch, 5ch, 6ch)

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 6 units @ 120 V; 10 units @ 208 V; 11 units @ 230 V
- Power and Current: 266 W, 2.209 A @ 120 V, 60 Hz
- Power and Current: 255 W, 1.306 A @ 208 V, 60 Hz
- Power and Current: 258 W, 1.201 A @ 230 V, 50 Hz

## Certifications / Qualifications

- CE
- IP Rating: IP65, temporary outdoor/wet use

## What's Included

- STRIKE 1
- Seetronic Powerkon IP65 power cord
- Gel frame (8.87 in/225 mm accessories)

## Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Seetronic Powerkon power linking cables
- 5-pin IP or Non-IP DMX Cables

- Multi-Bracket

- Strike 1 Multi-Bracket

## Required Accessories