

# COLORado™ 1 Tri-7 Tour



Compact and sturdy, COLORado™ 1 Tri-7 Tour is ideal for installation in tight locations without a compromise in output. Equipped with 7 tri-color RGB 3 W LEDs, it features a color temperature range of 2800 to 10000 K. The 16-bit dimming of each color (and master dimmer) sets it apart from every other light in its class. Double-bracket yoke doubles as floor stand for usage flexibility. COLORado™ 1 Tri-7 Tour also has Neutrik® powerCON® power in/out connectors, and 3- and 5-pin DMX connections.

## FEATURES

- Built-in auto and custom programs recalled via DMX and Master/Slave
- RGB color mixing via DMX or manually
- Color temperature presets, from 2800 to 10000 K
- 3-pin and 5-pin DMX input/output connections
- 16-bit dimming resolution for smooth fades
- Variable electronic dimmer (0–100%)
- 5 distinct dimming curves
- LED display with password protection
- Neutrik® powerCON® power input/output connections
- Simple and complex DMX channel profiles for programming versatility
- Double-bracket yoke doubles as floor stand
- Small size for easy installation into tight locations

## SPECIFICATIONS

- DMX Channels: 3, 4, 5, 9 or 13
- Data Connectors: 3- and 5-pin XLR
- Light Source: 7 LEDs (tri-color RGB) 3 W, (700 mA), 50,000 hours life expectancy
- Accessory Holder/  
Gel Frame Size: 6.25 in (159 mm)
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color  
Mixing: Yes
- Color Temperature  
Presets: Yes
- Installed Optics: 16°
- Beam Angle: 15°
- Field Angle: 28°
- Dimming Modes: 8
- Illuminance: 392 lux @ 5 m
- Color Temperature  
Range: 2800 to 10000 K
- IP Rating: IP20 dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON
- Power Output: Neutrik® powerCON®
- Power Linking: 25 units @ 120 V; 42 units @ 208 V; 48 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 44 W, 0.37 A @ 120 V, 60 Hz
- Power and Current: 46 W, 0.22 A @ 208 V, 60 Hz
- Power and Current: 47 W, 0.20 A @ 230 V, 50 Hz
- Weight: 7.7 lb (3.5 kg)
- Dimensions: 8.7 x 6.9 x 10.2 in (220 x 175 x 258 mm)
- Approvals: CE, MET