

# Q-Wash™ 419Z-LED



Q-Wash™ 419Z-LED is a moving yoke wash using 19 quad-color RGBW LEDs each at 15-watts, fitted for the production, touring, theatrical, installation and corporate rental markets. It produces a full range of bold saturated colors and variable whites. Built-in color macros and three individually controlled LED zones make for great visual effects. Q-Wash™ 419Z-LED is equipped with a smooth flicker-free dimming curve and a versatile 12.5- to 45-degree zoom, making it excellent for the demands of entertainment and installation production.

## FEATURES

- RGBW quad-color LEDs
- Smooth zoom and pan/tilt movement
- 3 zones of LED control
- 16-bit control of master dimmer and individual colors
- Flicker-free operation

## SPECIFICATIONS

- DMX Channels: 8, 10, 21, 21 or 34
- Data Connectors: 3- and 5-pin XLR
- Light Source: 19 LEDs (quad-color RGBW) 15 W (1 A), 50,000 hours life expectancy
- Pan and Tilt: 540°/270°
- Automatic Pan/Tilt Correction: Yes
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 7° to 30°
- Field Angle: 12.5° to 45°
- Viewing Angle: 120°
- Zoom Angle: 12.5° to 45°
- Dimming Modes: 8
- Illuminance (12.5°): 9,130 lux @ 5 m
- Illuminance (45°): 645 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 9 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 322 W, 2.64 A @ 120 V, 60 Hz
- Power and Current: 307 W, 1.52 A @ 208 V, 60 Hz
- Power and Current: 304 W, 1.4 A @ 230 V, 50 Hz
- Weight: 22 lb (10 kg)
- Dimensions: 11.6 x 10.6 x 14.5 in (297 x 270 x 369 mm)
- Approvals: CE, MET