

# Amhaze Stadium

## FEATURES

- Professional water-based haze machine
- 30-sec heat up time nearly eliminates wait time for operation
- Adjustable vent louver for directional haze flow
- Tour-ready with a rugged road case and M12 threaded rigging insert
- Efficient fluid consumption lasts up to 11 hours on a single fluid container
- Achieve continuous variable haze output and blower speed, adjusted via DMX or manual knobs

## SPECIFICATIONS

### DYNAMIC EFFECTS

- Fan Speed: 157 cfm
- Low Fluid Shutdown: Yes

### CONSTRUCTION / PHYSICAL

- Dimensions: 20.60 in (523.42 mm) x 10.80 in (274.9 mm) x 15.97 (405.7 mm)
- Weight: 38.4 lb (17.4 kg)
- Threaded Bolt: M12
- Exterior Color: Black
- Tank Capacity: 1.3 gal (4.92l)
- Fluid Consumption: 9.5 ml/min (0.15 gallons/hour)
- Maximum Run time: >8.25 hours @ full volume

### CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

### CONTROL

- Control Protocol: DMX
- DMX Channels: 2
- Modes/Personalities: 1 personality
- On-Board Control: Yes

### ELECTRICAL

- Input Voltage: 120 VAC, 50/60 Hz or 230 VAC, 50 Hz
- Power and Current: 1,230 W, 10.25 A @ 120 V, 50/60 Hz
- Power and Current: 2,430 W, 10.56 A @ 230 V, 50 Hz
- Heat-up Time: 30 sec

### CERTIFICATIONS / QUALIFICATIONS

- CE, MET, RCC, RoHS
- MET Listing Number: E115095



- US Safety: UL 499
- Canadian Safety : CSA C22.2 No. 64-10
- IP Rating: IP20, dry location
- Minimum distance from flammable material to all exterior surfaces of the product: 3.3 ft (1 m)
- Maximum exterior surface temperature (Tc): 127 °F (53 °C)

## WHAT'S INCLUDED

- Amhaze Stadium
- Seetronic Powerkon IP65 power cord
- Warranty Card
- Quick Reference Guide or User Manual

## OPTIONAL ACCESSORIES

- [Clamps](#)
- [Neutrik® powerCON® cables](#)
- [DMX Cables](#)