

Cloud 9

FEATURES

- Professional fogger gives high-impact low-lying fog effect on stage or in ballrooms
- Continuous operation produces fog to cover 3,230 ft² (300 m²) area
- Ultrasonic agitator combines distilled water with fog to produce low-lying fog effect
- Ships in rugged flight case with locking casters with hinged top cover to allow for operation even when closed
- Control via on board digital display or DMX
- Integrated water drain system makes cleanup fast and easy
- Use the low-lying fog fluid (LLG) to product the CO₂ effect, which lasts for several minutes before dissipating
- Use without dry ice or CO₂, so no special licensing/training required



SPECIFICATIONS

DYNAMIC EFFECTS

- Output: 15,000 cfm
- Low Fluid Shutdown: Yes
- HDF- Best overall performance for a medium to large coverage area. Fog dissipates after lifting into the air.
- PHF- Great dual-purpose effect. Good coverage area. Fog lifts into the air to become haze.

CONSTRUCTION / PHYSICAL

- Dimensions: 33.85 x 19.29 x 24.80 in (860 x 490 x 630 mm)
- Output Nozzle (outer diameter): 4.76 in (121 mm)
- Hose Length (fully extended): 8 ft (2.44 m)
- Weight: 121.3 lb (55.8 kg)
- Exterior Color: Black
- Fluid Tank Capacity: 0.92 gal (3.5 l)
- Water tank Capacity: 5.3 gal (20 l)
- Fluid Consumption: 29 ml/min (0.007 gal/min)
- Water Consumption (distilled): 165 ml/min (0.044 gal/min)
- Maximum Run Time: 2 hours max runtime @ 100% output

CONNECTIONS

- Power Connection: Edison plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65 (2x 120 V, 1x 230 V)
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX,
- DMX Channels: 2
- Modes/Personalities: 1 personalities (2)

- On-Board Control: Yes

ELECTRICAL

- Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz
- Power and Current (input A): 1000 W, 8.36 A @ 120 V, 60 Hz (120 V version)
- Power and Current (input B): 1130 W, 9.40 A @ 120 V, 60 Hz (120 V version)
- Power and Current: 2,600 W, 11.3 A @ 230 V, 50 Hz (230 V version)
- Heat-up Time: 3 min
- Breaker Size: 15 A (Input A, 120 V version)
- Breaker Size: 20 A (230 V version)

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)
- Thermal Dissipation @ 120V: 7,265 BTU per hour (max)
- Thermal Dissipation @ 230V: 8,870 BTU per hour (max)

WHAT'S INCLUDED

- Cloud 9
- 2 Seetronic Powerkon IP65
- Directional hose and hose clamp
- Overflow polyurethane tubing, 8.5 mm, 3ft (0.9 m)

OPTIONAL ACCESSORIES

- [Neutrik powerCON TRUE1 cables](#)
- [DMX Cables](#)