

COLORado M Solo

FEATURES

- Zooming RGBW LED wash for touring, rental and production indoors or out
- Completely homogenized wash with superior color mixing and zoom
- 4° to 24° smooth and fast zoom
- All environment operation with IP rated power and DMX connections
- Color temperature presets, from 3,200 K to 10,000 K
- Selectable, smooth dimming curves for programming versatility
- OLED display with password protection



SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (quad-color RGBW) 40W, (2.55 A), 50,000 hours life expectancy
- Beam Angle: 4° to 18°
- Field Angle: 5° to 24°
- Zoom Range: 4° to 24°
- Illuminance (4°): 4280 lux @ 5 m
- Illuminance (18°): 238 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 2400 Hz, 6000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 5
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 13.03 x 7.32 x 5.31 in (331x186x135 mm)
- Weight: 7.8 lb (3.6 kg)
- Exterior Color: Black
- Housing Material: Magnesium
- Accessory Holder/Gel Frame Size: 4.75 in (121 mm)

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65

- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX
- DMX Channels: 9, 12 or 17
- Modes/Personalities: 4 personalities (HSIC, SSP, TOUR, TR16)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 39 units @ 120 V; 58 units @ 208 V; 62 units @ 230 V
- Power and Current: 44 W, 0.342 A @ 120 V, 60 Hz
- Power and Current: 48W, 0.234 A @ 208 V, 60 Hz
- Power and Current: 49 W, 0.218 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

WHAT'S INCLUDED

- [Seetronic Powerkon IP65 power cord](#)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- [Neutrik TRUE1 power linking cables](#)
- [5-pin IP Rated DMX Cables](#)
- Color Blending Filters: DF60X1D, DF20D