

COLORdash Accent Quad

FEATURES

- Quad-color LED - red, green, blue, amber (RGBA)
- RGBA color mixing via DMX or manually
- Extremely compact with excellent output
- Variable electronic dimmer (0-100%)
- Simple and complex DMX channel profiles for programming versatility
- Double-bracketed yoke doubles as floor stand
- Easy to use OLED digital display
- Built-in auto programs recalled via DMX or Master/Slave



SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (quad-color RGBA) 10 W, (700 mA), 50,000 hours life expectancy
- Beam Angle: 15°
- Field Angle: 29°
- Illuminance (total): 140 lux @ 5 m
- PWM Frequency: 1,200 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 33 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 4.3 x 2.6 x 6.8 in (110 x 67 x 172 mm)
- Weight: 1.8 lb (0.8 kg)
- Exterior Color: Black

CONNECTIONS

- Power Connection: Edison plug to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
- Cable Length (power): 3.5 ft (1.07 m)

CONTROL

- Control Protocol: DMX
- DMX Channels: 4, 6 or 10
- Modes/Personalities: 3 personalities (4CH, 6CH, 10CH)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 14 W, 0.20 A @ 120 V, 60 Hz
- Power and Current: 14 W, 0.13 A @ 208 V, 60 Hz
- Power and Current: 13 W, 0.12 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP20, dry location

WHAT'S INCLUDED

- COLORDash Accent Quad

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- [5-pin DMX Cables](#)