

COLORdash Accent 3

FEATURES

- Quad-color (RGBA) compact LED wash
- Extremely compact with excellent output
- Variable electronic dimmer (0-100%)
- Simple and complex DMX channel profiles with RDM for programming versatility
- Double-bracketed yoke doubles as floor stand
- Easy to use OLED digital display
- Replaceable filter for additional beam angles
- Built-in auto programs recalled via DMX or Master/Slave

SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (quad-color RGBA) 20 W, (950 mA), 50,000 hours life expectancy.
- Installed Optics: 7°
- Beam Angle w/ filter: 14°
- Field Angle w/ filter: 27°
- Beam Angle w/o filter: 9°
- Field Angle w/o filter: 16°
- Lumens: w/o filter: 377 lm
- Lumens: w/ filter: 393 lm
- Illuminance (total) w/ filter: 175 lux @ 5 m
- Illuminance (total) w/o filter: 486 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 5
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 163 x 133 x 80 mm
- Weight: 2.0 lb (0.9 kg)
- Exterior Color: Black

CONNECTIONS

- Power Connection: Edison plug to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM



- DMX Channels: 4, 7 or 11
- Modes/Personalities: 3 personalities (4, 7, 11)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 18 W, 0.141 A @ 120 V, 60 Hz
- Power and Current: 21 W, 0.098 A @ 208 V, 60 Hz
- Power and Current: 20 W, 0.087 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP20, dry location

WHAT'S INCLUDED

- COLORDash Accent 3

OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables