

# IP Tester

## FEATURES

- Portable, compact IP testing device capable of both vacuum and pressure testing parameters.
- Pre loaded testing personality files for CHAUVET Professional IP rated products
- Easy to build custom testing profiles
- Built in webserver to easy connection to PC computers for creating fixture profiles and storing information from tests
- USB-C input for easy software upgrades and for storing fixture test data
- USB-B port for easy connection to PC
- Compact and impact resistant ABS plastic case is designed to fit in tool and road cases with touring in mind



## SPECIFICATIONS

### CONSTRUCTION / PHYSICAL

- Dimensions: 14.38 x 11 x 7.5 in (365.25 x 279.4 x 190.5 mm)
- Weight: 9.4 lb (4.3 kg)
- Exterior Color: Black
- Housing Material: Injection molded case

### CONNECTIONS

- Power Connection: Edison plug to Seetronic Powerkon
- Power Input: Seetronic Powerkon
- Quick-Release Air Hose Fitting
- Air In/Out Vent
- Data Connection: USB-B Port, USB-C
- Cable Length (power): 5 ft (1.5 m)

### CONTROL

- 6 button LCD menu
- Built in webserver for USB connection to PC
- remote information storage over USB-C input

### ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 25 W, 0.335 A @ 120 V, 60 Hz
- Power and Current: 25 W, 0.214 A @ 208 V, 60 Hz
- Power and Current: 25 W, 0.205 A @ 230 V, 50 Hz

### WHAT'S INCLUDED

- IP Tester
- Neutrik powerCON TRUE1 power cord
- USB Cable
- M12 Threaded Brass Nozzle with Push-to-Connector Fitting
- (2) M12 threaded metal plugs