

Ovation E-260WW IP

FEATURES

- Warm white ERS-style fixture with output exceeding a tungsten 750 W source
- Fully IP65 rated for seasonal use indoors or out
- Use of our standard Ovation beam shaping shutters and lenses lends familiarity and ease of use to the fixture
- Ultra smooth 16-bit dimming, and 8-bit dimming curves to complement any lighting scheme.
- Flat, even field of light for superior gobo projection
- RDM (Remote Device Management) for added flexibility
- Adjustable PWM (Pulse Width Modulation) to avoid flickering on camera

SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (WW) 230 W, (3.6 A), 3149 K, 50,000 hours life expectancy
- Color Temperature (at full): 3149 K
- CRI: 96
- Beam Angle (w/5° lens): 6°
- Beam Angle (w/10° lens): 8°
- Beam Angle (w/14° lens): 11°
- Beam Angle (w/19° lens): 13°
- Beam Angle (w/26° lens): 16°
- Beam Angle (w/36° lens): 20°
- Beam Angle (w/50° lens): 28°
- Beam Angle (w/15°–30° lens)(Narrow): 12°
- Beam Angle (w/15°–30° lens)(Wide): 14°
- Beam Angle (w/25°–50° lens)(Narrow): 21°
- Beam Angle (w/25°–50° lens)(Wide): 22°
- Field Angle (w/5° lens): 7°
- Field Angle (w/10° lens): 10°
- Field Angle (w/14° lens): 14°
- Field Angle (w/19° lens): 18°
- Field Angle (w/26° lens): 25°
- Field Angle (w/36° lens): 34°
- Field Angle (w/50° lens): 50°
- Field Angle (w/15°–30° lens)(Narrow): 15°
- Field Angle (w/15°–30° lens)(Wide): 29°
- Field Angle (w/25°–50° lens)(Narrow): 26°
- Field Angle (w/25°–50° lens)(Wide): 46°
- Dimming Modes: 4
- Lumens (w/19° lens): 7,587
- Lumens (w/26° lens): 10,284
- Lumens (w/36° lens): 10,121
- Lumens (w/50° lens): 9,655
- Illuminance (w/5° lens): 41,400 lux @ 5 m



- Illuminance (w/10° lens): 23,000 lux @ 5 m
- Illuminance (w/14° lens): 14,149 lux @ 5 m
- Illuminance (w/19° lens): 9,256 lux @ 5 m
- Illuminance (w/26° lens): 6,910 lux @ 5 m
- Illuminance (w/36° lens): 4,053 lux @ 5 m
- Illuminance (w/50° lens): 1,703 lux @ 5 m
- Illuminance (w/15°–30° lens)(Narrow): 16,827 lux @ 5 m
- Illuminance (w/15°–30° lens)(Wide): 10,626 lux @ 5 m
- Illuminance (w/25°–50° lens)(Narrow): 7,210 lux @ 5 m
- Illuminance (w/25°–50° lens)(Wide): 3,295 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Color Temperature Presets: No
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions (fixture only): 19.49 x 11.14 x 18.42 in (495 x 342 x 506 mm)
- Dimensions (w/5° lens extended): 43.58 x 14.17 x 14.48 in (1107 x 360 x 368 mm)
- Dimensions (w/10° lens extended): 34.88 x 12.16 x 12.48 in (886 x 309 x 317 mm)
- Dimensions (w/14° lens extended): 28.7 x 11.14 x 18.42 in (790 x 342 x 506 mm)
- Dimensions (w/26° lens extended): 23.5 x 13.46 x 19.92 in (597 x 342 x 506 mm)
- Dimensions (w/15°–30° lens): 32.87 x 14.61 x 14.61 in (835 x 371 x 371 mm)
- Dimensions (w/25°–50° lens): 27.17 x 14.61 x 14.61 in (690 x 371 x 371 mm)
- Weight (fixture only): 20.2 (9.2 kg)
- Weight (w/5° lens): 26 lb (11.9 kg)
- Weight (w/10° lens): 24 lb (11 kg)
- Weight (w/14° lens): 25.6 lb (11.6 kg)
- Weight (w/26° lens): 24.4 lb (11 kg)
- Weight (w/15°–30° lens): 34.2 lb (15.5 kg)
- Weight (w/25°–50° lens): 31.8 lb (14.4 kg)
- Exterior Color: Black
- Gobo Size (Optional): "A": 100 mm (outside), 75 mm (image), 2.5 mm (max. thickness)
- Gobo Size (Optional): "B": 86 mm (outside), 64.5 mm (image), 2.5 mm (max. thickness)
- Accessory Holder/Gel Frame Size (5° lens): 14 in (356 mm)
- Accessory Holder/Gel Frame Size (10° lens): 12 in (304 mm)
- Accessory Holder/Gel Frame Size (14° lens): 7.5 in (191 mm)
- Accessory Holder/Gel Frame Size (19°, 26°, 36°, and 50° lens): 6.25 in (159 mm)
- Accessory Holder/Gel Frame Size (15°–30° lens): 7.5 in (191 mm)
- Accessory Holder/Gel Frame Size (25°–50° lens): 7.5 in (191 mm)

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 2, 3, 4 or 7
- Modes/Personalities: 4 personalities (2, 3, 4, 7)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 7 units @ 120 V; 12 units @ 208 V; 13 units @ 230 V
- Power and Current: 221 W, 1.85A @ 120 V, 60 Hz
- Power and Current: 215 W, 1.11 A @ 208 V, 60 Hz
- Power and Current: 213 W, 1.01 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE® valve

WHAT'S INCLUDED

- Ovation E-260WW IP
- [Seetronic Powerkon IP65 power cord](#)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- [Neutrik powerCON cables](#)
- [3-pin or 5-pin DMX Cables](#)
- Color Blending Filters: DF60X1D, DF20D
- RDM2go
- Ovation Zoom Lenses: OHDZOOM1530, OHDZOOM2550
- Gobo Holder: [Ovation GR-1IP](#), Standard "S4" size Sandwich Style or Iris Slot Style gobo holder for "A" or "B" size gobos