# **Ovation FTD-55WW** FEATURES

- Track-mountable and dimmable 3" LED Fresnel
- Soft and even field of light
- Virtually silent operation for use in any situation
- Manually controlled variable zoom range between 20° to 75°

## **SPECIFICATIONS**

#### **OPTICAL**

- Light Source: 1 LED (WW) 36 W, (740 mA), 3200 K, 50,000 hours life expectancy
- Color Temperature (at full): 3200 K
- CRI: 91
- Beam Angle: 18° to 56°Field Angle: 30° to 69°
- Zoom Range: 20° to 75°
- Lumens (30°): 795
- Lumens (69°): 1,920
- Illuminance (30°): 279 lux @ 5 m
  Illuminance (69°): 100 lux @ 5 m

#### DYNAMIC EFFECTS

• Dimmer: Electronic

• Zoom: Manual

#### **CONSTRUCTION / PHYSICAL**

- Dimensions: 10.87 x 6.81 x 6.53 in (276.3 x 173 x 166 mm)
- Weight: 4 lb (1.9 kg)Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 3.26 in (83 mm)

#### CONNECTIONS

- Power Connection: Track Type H
- Cable Length (power): 1.5 ft (0.45 m)

#### CONTROL

• Control Protocol: Dimmer

#### **ELECTRICAL**

- Input Voltage: 120 VAC, 60 HzInput Voltage: 230 VAC, 50 Hz
- Power and Current: 31 W, 0.257 A @ 120 V, 60 Hz
- Power and Current: 30 W, 0.133 A @ 230 V, 50 Hz

#### **CERTIFICATIONS / QUALIFICATIONS**





- CE, MET
- IP Rating: IP20, dry location

### **WHAT'S INCLUDED**

- Ovation FTD-55WW
- Track adaptor
- Gel Frame
- Barn Doors

## **OPTIONAL ACCESSORIES**

• Color Blending Filters: DF60X1D, DF20D

