

# Ovation GR-1 Adapter

## FEATURES

- Power and data interface to adapt [Ovation GR-1IP](#) to any ERS-style fixture
- Utilize power from powerCON output of the ERS-style fixture
- Easily secure to the yoke of the ERS-style fixture
- On-board display for simple manual operation or DMX addressing
- 5-pin DMX in and thru for easy control from your console
- Requires [Ovation GR-1 IP](#) for operation (sold separately)



## SPECIFICATIONS

### CONSTRUCTION / PHYSICAL

- Dimensions: 3.7 x 2.1 x 5.3 in ( 95 x 53.1 x 135.7 mm)
- Weight: 0.6 lb (0.3 kg)
- Exterior Color: Black
- Housing Material: High-impact, flame retardant polymer, Steel

### CONNECTIONS

- Power Connection: Neutrik powerCON linking
- Data Connectors: 5-pin XLR
- Cable Length (power): 2ft 6 in (0.792 m)

### CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 1
- Modes/Personalities: 1 personalities (1Ch)

### ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 6 W, .092 A @ 120 V, 60 Hz
- Power and Current: 5 W, .063 A @ 208 V, 60 Hz
- Power and Current: 5 W, .060 A @ 230 V, 50 Hz

### CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

### WHAT'S INCLUDED

- Ovation GR-1 Adapter
- Neutrik powerCON power linking cord