

REM-RB50CM IP Curve

FEATURES

- REM Rig Bar, used for both overhead hanging and ground stacking
- Works with CHAUVET REM video panels
- Included Clamp attachment bracket (DRB-CTC) allows for direct connection using M12 bolts in clamps using TRUSST CTC-50HC

SPECIFICATIONS

CONSTRUCTION / PHYSICAL

- Dimensions: 19.67 x 2.36 x 4.72 in (499.6 x 60 x 120 mm)
- Weight: 16.8 lb (7.62 kg)
- Exterior Color: Black
- Housing Material: Aluminum extrusion, stainless steel

CLAMP

- Load Capacity (Hanging): 1,760.6 lb (345 kg)
- Load Capacity (Stacking): 1,752.7 lb (795 kg)
- Recommended Shackle Sizes: : 1/2", 5/8"

CERTIFICATIONS / QUALIFICATIONS

- IP Rating: IP65, temporary outdoor/wet use

WHAT'S INCLUDED

- 1pc REM Rig Bar-50 cm (REM-F50CMIP)
- 1pc clamp attachment bracket (DRB-CTC)
- 1pc clamp bolt for TRUSST CTC-50HC

OPTIONAL ACCESSORIES

- VIP Signal Distributor, VIP Media Server
- ArKaos Media Master Express + KN software
- Controllers (optional): IRC, FCW, ACW, FCT, FCM
- Clamps
- Barn Doors
- Neutrik powerCON cables
- DMX Cables
- Flight Cases
- Etc.

