

# Rogue Outcast 2 Hybrid

## FEATURES

- Fully featured, IP65 rated, high powered Spot/Beam/Wash combination fixture with an Ushio 400 W, 6500 K with 6,000 hour life expectancy lamp, 2 gobo wheels, 2 layerable prisms, large zoom range, and lightweight aluminum/magnesium housing
- Individually controllable and layerable 5 facet linear and 8 facet round prisms for maximizing visual impact
- Frost and beam flattening options for even light distribution
- Tight 0.9° narrow beam angle for focused air effects
- Linear zoom of 0.9° to 20.7° in beam mode, 1.4° to 37.2° in spot mode and 5.4° to 41.7° in wash mode for coverage in any application
- 9 rotating and 13 static gobos for massive visual effect
- DMX and RDM protocol control
- True 1 compatible power input
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility
- USB-C port for uploading software



## SPECIFICATIONS

### OPTICAL

- \*Test lab conditions. May vary depending on several factors including but not limited to: Environmental conditions, power/voltage, usage patterns, (on/off power cycling), control, and dimming.
- Light Source: Ushio NSL-400L W lamp, 8000 K, 6,000 hours life expectancy
- Color Temperature (at full): 7009K
- Front Lens size: 160mm
- CRI: 86.1
- Beam Angle: 1.4° to 14.5° (Spot mode)
- Field Angle: 2.8° to 30° (Spot mode)
- Cutoff Angle: 3.5° to 37.2° (Spot mode)
- Beam Angle: 0.9° to 6.7° (Beam mode)
- Field Angle: 1.7° to 18.1° (Beam mode)
- Cutoff Angle: 2.1° to 20.7° (Beam mode)
- Beam Angle: 5.4° to 32.1° (Wash mode)
- Field Angle: 9.5° to 39.4° (Wash mode)
- Cutoff Angle: 11.9° to 41.7° (Wash mode)
- Zoom Range (Spot mode): 1.4° to 37.2°
- Zoom Range (Beam mode): 0.9° to 20.7°
- Zoom Range (Wash mode): 5.4° to 41.7°
- Lumens – Output: 16,033
- Illuminance (1.4°) : 790,297lux @ 5 m (Spot mode)
- Illuminance (37.2°) : 6,787 lux @ 5 m (Spot mode)
- Illuminance (0.9°) : 180,594 lux @ 15 m (Beam mode)
- Illuminance (20.7°) : 2,158 lux @ 15 m (Beam mode)
- Illuminance (9.1°) : 30,289 lux @ 5 m (Wash mode)

- Illuminance (41.7°)1,309 lux @ 5 m (Wash mode)

## DYNAMIC EFFECTS

- Pan and Tilt: 540°/260°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt
- Colors: 13 + White, split colors, continuous scroll at variable speeds
- Gobos (1): 9 + open (9 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobos (2): 13 + open (13 metal), continuous scroll at variable speeds
- Gobo Size: Gobo Wheel 1 (rotating): 16 mm (outside), 12 mm (image), 1.1 mm (max. thickness)
- Dimmer: Motorized
- Shutter/Strobe: Motorized
- Zoom: Motorized
- Focus: Motorized
- Frost: Motorized
- Prism (1): 5 Facets, motorized, rotating
- Prism (2): 8 Facets, motorized, rotating
- Move-in-Black: Yes

## CONSTRUCTION / PHYSICAL

- Dimensions: 14.41 x 10.04 x 27.76 in (366 x 255 x 705 mm)
- Weight: 54.4 lb (24.7 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, Aluminum diecast, High-impact flame-retardant polymer

## CONNECTIONS

- Power Connection: Bare-wired to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

## CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 20 or 25
- Modes/Personalities: 2 personalities (20, 25)

## ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 581 W, 4.95 A @ 120 V, 60 Hz
- Power and Current: 565 W, 2.76 A @ 208 V, 60 Hz
- Power and Current: 568 W, 2.53 A @ 230 V, 50 Hz

## CERTIFICATIONS / QUALIFICATIONS

- CE, MET, CB, UKCA
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## WHAT'S INCLUDED

- Rogue Outcast 2 Hybrid
- Seetronic Powerkon IP65 power cord
- 2 Omega brackets with mounting hardware

## OPTIONAL ACCESSORIES

- Clamps
- DMX Cables
- Flight Cases