

Rogue Outcast 1 Hybrid

FEATURES

- Fully featured, IP 65 rated, high powered Spot/Beam/Wash combination fixture with an USHIO 400W, 6500K with 6000 hour life expectancy lamp, 2 gobo wheels, 2 layerable prisms, and linear zoom
- Rugged housing designed to withstand the elements in a temporary outdoor setting
- Individually controllable and layerable 6 facet linear and 8 facet round prisms for maximizing visual impact
- Frost and beam flattening options for even light distribution
- Tight 2° narrow beam angle for focused air effects
- Linear zoom of 1° to 15.3° in beam mode, 2.2° to 29.1° in spot mode and 4.9° to 28.3° in wash mode for coverage in any application
- 9 rotating and 13 static gobos for massive visual effect
- DMX and RDM protocol control
- True 1 compatible power input



SPECIFICATIONS

OPTICAL

- Light Source: USHIO NSL-400 W lamp, 6632 K, 6,000 hours life expectancy
- Color Temperature (at full): 6483 K
- Beam Angle: 2.2° to 12.4° (Spot mode)
- Field Angle: 4.3° to 24.3° (Spot mode)
- Cutoff Angle: 5.2° to 29.1° (Spot mode)
- Beam Angle: 1° to 5.2° (Beam mode)
- Field Angle: 1.8° to 12.6° (Beam mode)
- Cutoff Angle: 2.1° to 15.3° (Beam mode)
- Beam Angle: 4.9° to 18° (Wash mode)
- Field Angle: 9.3° to 25.6° (Wash mode)
- Cutoff Angle: 12.4° to 28° (Wash mode)
- Zoom Range (Spot mode): 2.2° to 29.1°
- Zoom Range (Beam mode): 1° to 15.3°
- Zoom Range (Wash mode): 4.9° to 28.3°
- Lumens – Source: 14,575
- Lumens – Output: 9,263
- Illuminance (4.3°): 209326 lux @ 5 m (Spot mode)
- Illuminance (24.3°): 5742 lux @ 5 m (Spot mode)
- Illuminance (1.8°): 123,124 lux @ 15 m (Beam mode)
- Illuminance (12.6°): 3,517 lux @ 15 m (Beam mode)
- Illuminance (9.3°): 17,118 lux @ 5 m (Wash mode)
- Illuminance (25.6°): 1,570 lux @ 5 m (Wash mode)

DYNAMIC EFFECTS

- Pan and Tilt: 540°/260°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt
- Colors: 13 + white, split colors, continuous scroll at variable speeds
- Gobos (1): 9 + open (9 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

- Gobos (2): 13 + open (13 metal), continuous scroll at variable speeds
- Gobo Size: Gobo Wheel 1 (rotating glass): 15.9 mm (outside), 12 mm (image), 1.1 mm (max. thickness)
- Dimmer: Motorized
- Shutter/Strobe: Motorized
- Zoom: Motorized
- Focus: Motorized
- Frost: Motorized
- Prism: 6 Facets, motorized, rotating
- Prism: 8 Facets, motorized, rotating
- Move-in-Black: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 15.91 x 12.20 x 30.16 in (404 x 310 x 766 mm)
- Weight: 83.8 lb (38 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

CONNECTIONS

- Power Connection: Bare-wired to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 20 or 25
- Modes/Personalities: 2 personalities (20, 25)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 514 W, 4.329 A @ 120 V, 60 Hz
- Power and Current: 513 W, 2.501 A @ 208 V, 60 Hz
- Power and Current: 520 W, 2.267 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): 14 °F to 104 °F (-10 °C to 40 °C)

WHAT'S INCLUDED

- Rogue Outcast Hybrid IP
- Seetronic Powerkon IP65 power cord
- 2 Omega brackets with mounting hardware
- Quick Reference Guide