

STRIKE P38

FEATURES

- Intense single pod blinder/strobe rated IP65 for all-weather use
- Emulated “red shift” to mimic incandescent fixtures perfectly.
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on-the-fly
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM)
- RDM (Remote Device Management) for added flexibility



SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (WW) 90 W, (1.19 A), 2688 K, 50,000 hours life expectancy.
- Light Source: 8 LEDs (Amber) 5 W, (0.07 A), 50,000 hours life expectancy.
- Color Temperature (at full): 2754 K
- Color Temperature (at 10%): 1899 K
- CRI: 92
- Beam Angle: 27°
- Field Angle: 51°
- Lumens: 2,186
- Illuminance: 325 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Strobe Rate: 0 to 29 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 11.93 x 10.27 x 7.25 in (303 x 261 x 184 mm)
- Weight: 8.4 lb (3.8 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 6.25 in (159 mm)

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Protocol(s): DMX, RDM
- DMX Channels: 1, 3, 4, 5 or 6
- Modes/Personalities: 5 personalities (1ch, 3ch, 4ch, 5ch, 6ch)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 30 units @ 120 V; 50 units @ 208 V; 55 units @ 230 V
- Power and Current: 54 W, .449 A @ 120 V, 60 Hz
- Power and Current: 56 W, .267 A @ 208 V, 60 Hz
- Power and Current: 58 W, .245 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- STRIKE P38
- Seetronic Powerkon IP65 power cord
- Gel frame (6.25 in/158.75 mm accessories)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- Seetronic Powerkon power linking cables
- 5-pin IP or Non-IP DMX Cables
- Ovation F6.25 Barndoor